



CONTENTS

DISCOVER STARFLOOR CLICK IS & 55PLUS	04
DESIGN & INSPIRATION	•••••••
ime Oak	06
lpine Oak	08
egacy Pine	10
Rough Concrete	12
Brushed Pine	14
inglish Oak	16
Modern Oak	18
intage Zinc	20
Candinavian Oak	22
Contemporary Oak	24
ntik Oak	26
Composite	28
Vhite oak	30
ACCESSORIES	32
SUSTAINABILITY	34
ECHNICAL INFORMATION	35
	30

DISCOVER STARFLOOR CLICK 55 & 55PLUS

Starfloor Click 55 & 55PLUS with Extra Matt effect

Matt elegance for an aura of authenticity. Elegance you'll call home.

Extra Matt, extra elegant finish

Create a more homely atmosphere with Tarkett's Starfloor Click 55 & 55 PLUS. Its elegant Extra Matt finish reinforces the authentic beauty of a room's atmosphere. And with soft, muted hues, it's also the perfect complement to bright furniture that brings life to a room whether a bathroom, a kitchen, or a living room.

That's not all. With a select range of naturallooking colours and realistic looks such as wood, stone and concrete, Starfloor Click 55 & 55PLUS offers subtle designs that are carefully handcrafted in Europe to help you choose a room's ambiance, anywhere in the house.

Eternally beautiful

Rest assured, there's nothing fleeting about Starfloor Click 55's style and 55PLUS's style. Backed by a twenty-year warranty, the vinyl flooring includes a durable professional-grade wear layer. Treated with Top Clean surface protection, it offers increased resistance to your kitchen, hallway, child's room and indeed all high traffic spaces where scuffs, scratches and stains happen, not to mention how easy it is to clean and maintain.





Starfloor Click 55 without Extra Matt effect

Starfloor Click 55 with new Extra Matt effect

Installed with a click

Installing Starfloor Click 55 & 55Plus has never been so fast and easy thanks to the fold-down click system. From tiles to three lengths of planks, (all with four-sided bevelling), you can opt for an acoustic underlay for additional sound absorption and matching skirtings for that final polish.

Designed for life...

Starfloor Click 55 and 55PLUS is one step ahead when it comes to making an impact on people and the planet. Designed to be returned, recycled, remanufactured or reused, it's 100% recyclable. And since the VOC levels of our floorings are 10 to 100 times lower than the strictest European standards, they can contribute to your well-being with better indoor air quality.

No matter what you like, Starfloor Click 55 & 55PLUS with Extra Matt effect

has everything to embody a natural, soothing ambience. Simply put, it's matt elegance with an aura of authenticity.



LIME OAK Lime Oak

This flooring feels like a good friend: always there but never intrusive. The well balanced design is coming in nine coordinated colour shades from white to black to match every interior style. A perfect starting point to create exciting ambiances based on a timeless but contemporary design.









0V, with MOQ of 6 pallets



2V, with MOQ of 6 pallets **4V,** standard





White 35954048 Corresponding skirting 26640761



Light Beige 35954049 Corresponding skirting 26640762



Beige 35954050 Corresponding skirting 26640763



Natural 35954051 Corresponding skirting 26640764



Grey 35954052 Corresponding skirting 26640765



Grege 35954053 Corresponding skirting 26640766



Dark Grey Corresponding skirting 26640767



Corresponding skirting 26640768



Corresponding skirting 26640769



ALPINE OAK Maggiore

From the mountain lodge to your home. Alpine Oak is catching the rough and worn feeling of a hideaway surrounded by pure nature. The colours are a reminder on the natural aging of wood and the tactile surface, which follows the structure of the wood grains, thanks to the Plus effect.









OV, with MOQ of 6 pallets





2V, with MOQ of 6 pallets **4V,** standard



Natural Corresponding skirting 26640770



Brown 35955058 Corresponding skirting 26640771



Corresponding skirting 26640772



Black Corresponding skirting 26640773



White Corresponding skirting 26640774



LEGACY PINE

Pine

Authenticity for wood lovers. The nearly unfinished look of the Legacy Pine is a reference to the reclaimed materials which delivers a warm atmosphere but with an industrial twist. The colours are like aged or bleached from time and weather which is supported by the registered surface embossing.









OV, with MOQ of 6 pallets







2V, with MOQ of 6 pallets **4V,** standard



Light Grey 35954154 Corresponding skirting 26640775



Medium Grey 35954155 Corresponding skirting 26640776



Corresponding skirting 26640777



Brown 35954157 Corresponding skirting 26640778



ROUGH CONCRETE

Beton brut

Concrete has been the favorite material of architects since a long time for a reason. No other material is that classic and modern at the same time. The Rough Concrete is an example of the puristic impression but also delivering homeliness through the colour range.









0V, with MOQ of 6 pallets **2V,** with MOQ of 6 pallets **4V,** standard









White Corresponding skirting 26640779



Grey 35957159 Corresponding skirting 26640780



Corresponding skirting 26640781



Black Corresponding skirting 26640782



BRUSHED PINE

Rustic

A decor like a garden picnic. Signs of usage but also parts which could be bleached from the sunlight are part of this design. Light colours which could be inspired from a nordic summer are completing this feeling.











0V, with MOQ of 6 pallets **2V,** with MOQ of 6 pallets **4V,** standard



Grey Corresponding skirting 26640614



Natural 35950015 Corresponding skirting 26640265



Corresponding skirting 26640266



ENGLISH OAK

Natural

A noble oak pattern with a rustic touch. English Oak is working very well with design codes around country living and the simplicity of raw ambiances with added patina.







0V, with MOQ of 6 pallets **2V,** with MOQ of 6 pallets **4V,** standard







Beige Corresponding skirting 26640624



Grey Beige 35950029 Corresponding skirting 26640268



35950027 Corresponding skirting 26640627



Light Beige 35950028 Corresponding skirting 26640267



MODERN OAK

Natural

Classic pattern which is as timeless as the colour range. Modern Oak is fitting every demand and lifestyle. The natural surface structure provides a natural feel and touch and is adding serenity to every interior.







0V, with MOQ of 6 pallets **2V,** with MOQ of 6 pallets **4V,** standard







White Corresponding skirting 26640394



Classical 35950146 Corresponding skirting 26640396



Beige 35950145 Corresponding skirting 26640395



VINTAGE ZINC

Flat

This classic metal design is adding a vintage look to every space without being superficial. The colours are inspired by the natural patina of metals with marks of wear and tear.







0V, with MOQ of 6 pallets **2V,** with MOQ of 6 pallets **4V,** standard







Black 35952094 Corresponding skirting 26640287



Rust Corresponding skirting 26640288



Silver Corresponding skirting 26640289



SCANDINAVIAN OAK

Weathered

Wide grains with the touch of white oiling and a colour range of warm beige and cold grey shades are representing the nordic decoration style. The colour shades are paying attention to this Scandinavian appearance.







OV, with MOQ of 6 pallets





2V, with MOQ of 6 pallets **4V,** standard



Dark Grey Corresponding skirting 26640338



Medium Grey 35950104 Corresponding skirting 26640337



Corresponding skirting 26640336



Dark Beige Corresponding skirting 26640335



Medium Beige Corresponding skirting 26640334



Light Beige 35950100 Corresponding skirting 26640333



CONTEMPORARY OAK

Natural

Beautiful balanced and a perfect stage for timeless interiors. With subtle gradients from light to dark inside the plank, this design is creating beautiful soft waves on the floor. Small details, which are never too obvious are completing this state-of-the-art design.















Brown 35951112 Corresponding skirting 26640349



Natural 35951111 Corresponding skirting 26640348



ANTIK OAK

Rustic

Vintage but modern. This design is following the trend of finding back materials from the past and turning them into new classic. Subtle sawmarks are underlining this timeless oak pattern to create ambiance which never go out of style.











0V, with MOQ of 6 pallets **2V,** with MOQ of 6 pallets **4V,** standard



Anthracite Corresponding skirting 26640262



Middle Grey 35951008 Corresponding skirting 26640263



Corresponding skirting 26640261



White Corresponding skirting 26640382



COMPOSITE

Beton

Perfect for minimalistic and industrial interiors with high contrast. Small scratches and cracks are making this decor look very natural. This decor is also a perfect fit with raw wood or metals.













0V, with MOQ of 6 pallets **2V,** with MOQ of 6 pallets **4V,** standard



Black Corresponding skirting 26640318



Cool Grey 35952073 Corresponding skirting 26640317



WHITE OAK Natural

White washed and limed for a appealing worn out look. This very natural pattern is a reference for the famous beach house look. In beautiful black this natural vintage touch is a beautiful highlight on every floor.













Dimensions: 19,05 x 121,1 cm

0V, with MOQ of 6 pallets **2V,** with MOQ of 6 pallets **4V,** standard



Black 35950153 Corresponding skirting 26640404

ACCESSORIES

UNDERLAYER - FAST-TRACK RENOVATION SYSTEMS



MARATHON® DUAL

- The ready-to-use solution for renovating over an existing subfloor
- Superior performance
- Easy to install and remove

DESCRIPTION

- Material: MDF and coniferous woods
- **Density:** 240kg per m³ • Total thickness: 6mm
- Article code: 24993020







UNDERLAYERS - FOR ACOUSTIC COMFORT









TARKOMFORT PREMIUM


- High-performance acoustic insulation: high-impact sound reduction (19 dB with iD Inspiration Click) and in-room noise reduction (72 dB).
- High-performance solution to improve static indentation resistance (0.18mm with iD Inspiration Click).
- · Quick and easy to install.

DESCRIPTION

- Material: viscoelastic polymer based on polyolefins and EVA
- Total weight: 100g per m² • Total thickness: 1mm • Article code: 2499 2030 - Black







- Enhanced durability thanks to its high-density, heavy-duty composition
- Simple to install solution with woven anti-slip surface to grip floor covering.

- Material: siliconised PET carrier film with high-resistance polyurethane layer and non-woven white fleece backing
- Total weight: 1.500g per m² • Total thickness: 1 5mm • Article code: 2499 2020
- Compatible with: LVT click (planks and tiles)

TRANSITION PROFILES




LVT TRANSITION STRIP GENERAL TRAFFIC

Aluminium transition strip for LVT Click & Loose-Lay used in general traffic areas.

Elegant finish with smooth surface and no visual screws. Bendable with radius 60 cm.

- Size: 24 mm wide x 6 mm high x 2700 mm long
- Packaging: Full kit including top profiles and dowls. 10 units of 2,7lm in a cardboard box = 27 lm






Silver NCS:S 2500-N	1451 021
Stainless steel NCS:S 6005-Y20R	1451 022



LVT BENDABLE STOP PROFILE

Aluminium stop profile to be screwed. Very resistant to wear & traffic Ribbed surface for slip-resistance Bendable with radius 80cm

- Size: 30 mm wide x 5 mm high inside x 8 mm high outside 30 mm high x 2500 mm long
- Packaging: Full kit including stop profiles, screws and dowls. 10 units of 2,5lm in a cardboard box = 25 lm






SKIRTINGS

PVC DECORATIVE SKIRTING

Compact skirting with decorative film and PUR surface treatment. Perfectly match all Starfloor Click 55 designs.



• Packaging: 2.02lm skirting in packs of 10



STARFLOOR CLICK55/55PLUS **SUSTAINABILITY**

DOING GOOD. TOGETHER.

Every day, we strive to improve people's lives, preserve natural resources and respect our environment. We focus on making products that deliver optimal performance, promote healthy living and preserve the planet's natural capital. Our design philosophy is inspired by the circular economy.



Designing for life

We design our flooring solutions for life, thereby contributing to people's well-being and good health as well as preserving natural resources.

People-friendly spaces

Respecting the environment

We apply Cradle-to-Cradle® principles. 96% of All of our vinyl sites in the European Union are materials used in our products are assessed by the equipped with closed-loop water systems today.

All Tarkett vinyl products manufactured in the European Union are close to 100% phthalate-free. Starfloor Click 55/55+ also have ultra low VOC emissions for optimal indoor air quality.



Closing the loop

Starfloor Click 55 and 55+ contain between 21% and 36% recycled materials.

Starfloor Click 55 and 55+ are eligible for our ReStart® takeback programme. Through ReStart®, installation flooring waste can be effectively managed while contributing to safeguarding the world's natural resources and protecting the environment. We recycle customer flooring offcuts and waste from our production, transforming it into new, high quality products.

In this way, we can collectively close the loop and shift to a circular economy.



Driving collaboration

We seek ways to work more closely with our customers, suppliers and industry partners as we believe in a collaborative approach to respond to global challenges. We promote transparency about our sustainability progress, products and ambitions by voluntarily disclosing product information.

TECHNICAL DATASHEET

TECHNICAL DATA	STANDARD	STARFLOOR CLICK 55	
CLASSIFICATION			
Classification	EN ISO 10582	Heterogeneous Compact Resilient Floorcovering	
	EN ISO 10874	Residential: 23 - Commercial: 33	
Wear layer binder content	EN ISO 10582	Type I	
TECHNICAL CHARACTERISTICS			
Total thickness	EN ISO 24346	4.5 mm	
Total weight	EN ISO 23997	8 kg/m²	
Wear layer thickness	EN ISO 24340	0.55 mm	
Locking system		Click	
Bevelled edges		Yes	
Surface treatment (PUR)		Extreme®	
Form of delivery	EN ISO 24342 Planks	19.05 x 121.1 cm = 7 planks/box = 1.61 m ² /box 24.05 x 149.1 cm = 5 planks/box = 1.79 m ² /box	
	EN ISO 24342 Tiles	32.38 x 60.1 cm = 9 tiles/box = 1.75 m ² /box	
PERFORMANCES FOR CE MARKING REQUI	REMENTS (EN 14041)		
Declaration of Performance	EN 14041	0197-0010-DoP-2016-04	
Reaction to fire	EN 13501-1	B _f -s1 loose laid on concrete	
Electrostatic properties	EN 1815	≤ 2 kV on concrete	
Thermal resistance	EN ISO 10456	0.04 m ² K/W	
Slip resistance	EN 13893	μ ≥ 0.3	
TECHNICAL PERFORMANCES			
Dimensional stability	EN ISO 23999	≤ 0.10%	
Impact sound reduction	NF EN ISO 717 / 2	ΔL _w 3 dB	
Slip resistance	DIN 51130	R9 / R10 depending on embossing	
Locking strength [kN/m]	EN 10582	≥ 2 kN/m	
Furniture leg	EN 424	No damage	
Castor chair	ISO 4918 - EN 425	No damage	
Curl resultant to heat	EN ISO 23999	≤ 2 mm	
Light fastness	EN ISO 105-B02 (method 3ª)	≥ 6	
Residual indentation	EN ISO 24343-1	≤ 0.10 mm	
Chemical resistance	EN ISO 26987	Very good	
Underfloor heating		Suitable – max. 27°C	
Peeling resistance	EN ISO 24345	≥ 50N / 50mm	
ENVIRONMENTAL PERFORMANCES			
Total VOC emissions	ISO 16000-9	≤ 10 µg/m³ (after 28 days)	
COLOURS			
		28	

The above information is subject to modification for the benefit of further improvement. (10/18).

According to the European Regulation N° 305/2011 for CE Marking, the Declarations of Performance are available on our website www.tarkett.com

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.



















INT BE: 2800030001 / INT NL: 2800030002 / INT UK: 2800030003 / INT TDM: 2800030004 / INT EE: 2800030005 / INT LV: 2800030006 / INT KA: 2800030007 / INT CZ: 2800030008 / INT HG: 2800030009 / INT TME: 2800030010 / INT TK: 2800030011 / INT ROA: 2800030012 / INT DESIGN: 2800030019 / INT SAMPLING: 2800030020

Due to evolution of standards, characteristics indicated in the text and images in this document are not binding only after confirmation by our departments.

Design: Agence Gecko / Photos: Studio des Plantes / Evolution / Print: Altavia



