



A++/A+



18 / 24 / 36



48 / 60

MODELO			AUD-18UX4SZKL1	AUD-24UX4SALH1	AUD-36UX4SAMH1	AUD-48UX6SPHH	AUD-60UX6SPHH
UNIDAD INTERIOR			AUD-18UX4SKL1	AUD-24UX4SLH1	AUD-36UX4SMH1	AUD-48UX4SHH	AUD-60UX4SHH
UNIDAD EXTERIOR			AUW-18U4SZ1	AUW-24U4SA1	AUW-36U4SA1	AUW-48U6SP	AUW-60U6SP
<i>Performance</i>							
SEER			6,11	6,11	6,11	/	/
SCOP			4,01	4,01	4,01	/	/
Clasificación energética	Refrigeración		A++	A++	A++	A	A
	Calefacción		A+	A+	A+	A	A
Capacidad refrigeración (W)			5000(1200-6500)	7000(1500-7800)	9200(3600-10500)	14000(5500-13500)	17000(6200-18000)
Capacidad calefacción (W)			5600(1800-7200)	8100(1800-10000)	11000(3050-13800)	16000(4000-18000)	20500(6400-21000)
Capacidad Nominal (w)	Refrigeración		1500	2300	3050	3920	5295
	Calefacción		1600	2650	3250	4150	5650
circulación del aire (m3 Max)			850	1100	1800	2000	2000
EER refrigeración (w/w)			3,33	3,04	3,04	3,21	3,21
COP Calefacción (w/w)			3,50	3,06	3,06	3,61	3,63
<i>Alimentación</i>							
Volt/Phase/Hz			220-240V/1P/50Hz	220-240V/1P/50Hz	220-240V/1P/50Hz	380-415V/50Hz/3P	380-415V/50Hz/3P
Potencia Nominal	Refrigeración		6,8	10,2	13,9	7,5	10,8
	Calefacción		7,3	11,5	13,1	8,0	11,3
Nivel Presión sonora dB (A)	unidad interior	Alto \ Med \ Bajo	41/37/35	49/45/43	45/41/39	53/50/49	53/50/49
		Max	54	61	56	-	-
<i>Tubería</i>							
Diámetro (Líquido)		Pulg	1/4	3/8	3/8	3/8	3/8
Diámetro (Gas)		Pulg	1/2	5/8	5/8	3/4	3/4
Longitud máxima		m	15	30	30	50	50
Altura máxima		m	10	20	20	30	30
Altura desagüe		m	1,2	1,2	1,2	1,2	1,2
Dimensiones (LxAxP)		Unidad Interior	1170x190x447	900x270 x720	1300x270 x720	1300x350x800	1300x350x800
Peso neto		Unidad Interior	24	32	43	50	50
Dimensiones paquete (LxAxP)		Unidad Interior	1340x236x580	1170x340x870	1570x340x870	1550x410x940	1550x410x940
Peso bruto		Unidad Interior	28	37	51	58	58
Capacidad de carga (20' / 40' / 40HQ)			54/114/121	36/74/80	28/56/66	19/40/42	19/40/42
PVPR			1699 €	1999 €	2699 €	3499 €	4599 €